



**AGT**Technologies  
LCD Displays

## **SPECIFICATION**

# **AGM-035A0-D0-R**

Ver.01

Atualizado em 13/05/19.

## Updates and Reviews:

| VERSION | DATE       | DESCRIPTIONS                                 |
|---------|------------|----------------------------------------------|
| 00      | 23/08/2016 | First issue                                  |
| 01      | 08/05/2018 | Block diagram update and code system update. |
|         |            |                                              |
|         |            |                                              |
|         |            |                                              |
|         |            |                                              |
|         |            |                                              |
|         |            |                                              |
|         |            |                                              |

# **Contents**

- 1.Summary
- 2.General Specification
- 3.Absolute Maximum Ratings
- 4.Electrical Characteristics
- 5.DC Characteristics
- 6.Interface Timing Characteristics
- 7.Optical Characteristics
- 8.Interface
- 9.Block Diagram
- 10.Reliability
- 11.Touch Panel Information
- 12.Contour Drawing
- 13.Additional Resources
- 14.Codes System AGT TFT
- 15.Kit Information

# **1.Summary**

This technical specification applies to 3.5" color TFT-LCD panel. The 3.5" color TFT-LCD panel is designed for camcorder, digital camera application and other electronic products which require high quality flat panel displays. This module follows RoHS.

## **2.General Specifications**

| Item             | Dimension                         | Unit |
|------------------|-----------------------------------|------|
| Size             | 3.5 inch (Diagonal)               | inch |
| Dot Matrix       | 320 x 3(RGB) x 240                | dots |
| Module dimension | 93.5(H) x 63.80(V) x 8.61(D)      | mm   |
| Active area      | 72.3(H) x 54.56 (V)               | mm   |
| Dot pitch        | 0.073(H) X 0.219(V)               | mm   |
| LCD type         | TFT, Normally White, Transmissive |      |
| View Direction   | 12 o'clock                        |      |
| Backlight Type   | LED , Normally White              |      |
| Controller IC    | SSD1963                           |      |
| Interface        | Digital 8080 / 6800               |      |
| With /Without TP | With RTP                          |      |
| Surface          | Anti-Glare                        |      |

\*Color tone slight changed by temperature and driving voltage

## **3.Absolute Maximum Ratings**

| Item                  | Symbol | Min | Typ | Max | Unit |
|-----------------------|--------|-----|-----|-----|------|
| Operating Temperature | TOP    | -20 | --- | +70 | °C   |
| Storage Temperature   | TST    | -30 | --- | +80 | °C   |

Note: Device is subject to be damaged permanently if stresses beyond those absolute maximum ratings listed above

Temp.  $\leq 60^{\circ}\text{C}$ , 90% RH MAX. Temp.  $> 60^{\circ}\text{C}$ , Absolute humidity shall be less than 90% RH at  $60^{\circ}\text{C}$

## 4. Electrical Characteristics

### 4.1. Operating conditions:

| Item                   | Symbol | Condition | Min | Typ | Max | Unit | Remark |
|------------------------|--------|-----------|-----|-----|-----|------|--------|
| Supply Voltage For LCM | VDD    | ---       | 3.0 | 3.3 | 3.6 | V    | ---    |
| Power Supply For LCM   | IDD    | ---       | --- | 310 | 470 | mA   | Note 1 |

Note 1 : This value is test for VDD=3.3V, Ta=25°C


### 4.2. LED driving conditions (for external power supply when needed)

Backlight:

| Name                 | Min    | Type | Max  | Unit                      |
|----------------------|--------|------|------|---------------------------|
| Current              | 15     | 20   | 25   | mA                        |
| Voltage              | 18.0   | 19.2 | 22.0 | V                         |
| Power Consumption    | 300    | 384  | 450  | mW                        |
| Luminance            | 300    | 350  | -    | Cd/m <sup>2</sup> (Note1) |
| Luminance uniformity | 75%    | 80%  | -    |                           |
| X color Coordinates  | 0.27   | 0.28 | 0.31 | -                         |
| Y color Coordinates  | 0.27   | 0.28 | 0.31 | -                         |
| Led Life Time        | 50.000 | -    | -    | Hr (Note2)                |

Note1: This luminance is tested with assembling the LCD.

Note2: Brightness to be decreased to 50% of the initial value.



## 5. DC Characteristics

| Parameter                | Symbol | Rating |     |        | Unit | Condition |
|--------------------------|--------|--------|-----|--------|------|-----------|
|                          |        | Min    | Typ | Max    |      |           |
| Low level input voltage  | VIL    | 0      | -   | 0.3VDD | V    |           |
| High level input voltage | VIH    | 0.7VDD | -   | VDD    | V    |           |

## 6. Interface timing


### 6.1. 8080 Mode

The 8080 mode MCU interface consist of CS#, D/C#, RD#, WR#, Data bus. This interface use WR# to define a write cycle and RD# for read cycle. If the WR# goes low when the CS# signal is low, the data or command will be latched into the system at the rising edge of WR#. Similarly, the read cycle will start when RD# goes low and end at the rising edge of RD#.


### 6.2. 8080 Mode Write Cycle

| Symbol | Parameter                                        | Min      | Typ        | Max | Unit |
|--------|--------------------------------------------------|----------|------------|-----|------|
| fMCLK  | System Clock Frequency                           | 1        | —          | 110 | MHz  |
| tMCLK  | System Clock Period                              | 1/ fMCLK | —          | —   | ns   |
| tPWCSH | Control Pulse High Width Write                   | 13       | 1.5* tMCLK | —   | ns   |
|        | Read                                             | 30       | 3.5* tMCLK |     |      |
| tPWCSL | Control Pulse Low Width Write (next write cycle) | 13       | 1.5* tMCLK | —   | ns   |
|        | Write (next read cycle)                          | 80       | 9* tMCLK   |     |      |
|        | Read                                             | 80       | 9* tMCLK   |     |      |
| tAS    | Address Setup Time                               | 1        | —          | —   | ns   |
| tAH    | Address Hold Time                                | 2        | —          | —   | ns   |
| tDSW   | Write Data Setup Time                            | 4        | —          | —   | ns   |
| tDHW   | Write Data Hold Time                             | 1        | —          | —   | ns   |
| tPWLW  | Write Low Time                                   | 12       | —          | —   | ns   |
| tDHR   | Read Data Hold Time                              | 1        | —          | —   | ns   |
| tACC   | Access Time                                      | 32       | —          | —   | ns   |
| tPWLR  | Read Low Time                                    | 36       | —          | —   | ns   |
| tR     | Rise Time                                        | —        | —          | 0.5 | ns   |
| tF     | Fall Time                                        | —        | —          | 0.5 | ns   |
| tCS    | Chip select setup time                           | 2        | —          | —   | ns   |
| tCSH   | Chip select hold time to read signal             | 3        | —          | —   | ns   |

6.3. Parallel 8080-series Interface Timing Diagram (Write Cycle)



6.4. Parallel 8080-series Interface Timing Diagram (Read Cycle)



6.5. Pixel Data Format

| Interface            | Cycle           | D[15] | D[14] | D[13] | D[12] | D[11] | D[10] | D[9] | D[8] | D[7] | D[6] | D[5] | D[4] | D[3] | D[2] | D[1] | D[0] |
|----------------------|-----------------|-------|-------|-------|-------|-------|-------|------|------|------|------|------|------|------|------|------|------|
| 16 bits (565 format) | 1 <sup>st</sup> | R5    | R4    | R3    | R2    | R1    | G5    | G4   | G3   | G2   | G1   | G0   | B5   | B4   | B3   | B2   | B1   |
| 16 bits              | 1 <sup>st</sup> | R7    | R6    | R5    | R4    | R3    | R2    | R1   | R0   | G7   | G6   | G5   | G4   | G3   | G2   | G1   | G0   |
|                      | 2 <sup>nd</sup> | B7    | B6    | B5    | B4    | B3    | B2    | B1   | B0   | R7   | R6   | R5   | R4   | R3   | R2   | R1   | R0   |
|                      | 3 <sup>rd</sup> | G7    | G6    | G5    | G4    | G3    | G2    | G1   | G0   | B7   | B6   | B5   | B4   | B3   | B2   | B1   | B0   |
| 8 bits               | 1 <sup>st</sup> |       |       |       |       |       |       |      |      | R7   | R6   | R5   | R4   | R3   | R2   | R1   | R0   |
|                      | 2 <sup>nd</sup> |       |       |       |       |       |       |      |      | G7   | G6   | G5   | G4   | G3   | G2   | G1   | G0   |
|                      | 3 <sup>rd</sup> |       |       |       |       |       |       |      |      | B7   | B6   | B5   | B4   | B3   | B2   | B1   | B0   |

## 7.Optical Characteristics

| Item                                                    |       | Symbol     | Condition                                 | Min  | Typ  | Max  | Unit              | Remark            |
|---------------------------------------------------------|-------|------------|-------------------------------------------|------|------|------|-------------------|-------------------|
| Response time                                           |       | Tr         | $\theta = 0^{\circ}$ 、 $\Phi = 0^{\circ}$ | -    | 10   | -    | ms                | Note 3,5          |
|                                                         |       | Tf         |                                           | -    | 15   | -    | ms                |                   |
| Contrast ratio                                          |       | CR         | At optimized viewing angle                | 300  | 350  | -    | -                 | Note 4,5          |
| Color Chromaticity                                      | White | Wx         | $\theta = 0^{\circ}$ 、 $\Phi = 0$         | 0.26 | 0.31 | 0.36 | -                 | Note 2,6,7        |
|                                                         |       | Wy         |                                           | 0.28 | 0.33 | 0.38 | -                 | -                 |
| Viewing angle<br>(Gray Scale<br>Inversion<br>Direction) | Hor   | $\Phi$ R   | $CR \geq 10$                              | -    | 55   | -    | Deg.              | Note 1            |
|                                                         |       | $\Phi$ L   |                                           | -    | 55   | -    |                   |                   |
|                                                         | Ver   | $\Theta$ L |                                           | -    | 45   | -    |                   |                   |
|                                                         |       | $\Theta$ H |                                           | -    | 50   | -    |                   |                   |
| Brightness                                              |       | -          | -                                         | 300  | 350  | -    | cd/m <sup>2</sup> | Center of display |

Ta=25±2 °C, IL=20mA

Note 1: Definition of viewing angle range




Fig. 7.1. Definition of viewing angle

Note 2: Test equipment setup:

After stabilizing and leaving the panel alone at a driven temperature for 10 minutes, the measurement should be executed. Measurement should be executed in a stable, windless, and dark room. Optical specifications are measured by Topcon BM-7 or BM-5 luminance meter 1.0° field of view at a distance of 50cm and normal direction.

Note 3: Definition of Response time:

The response time is defined as the LCD optical switching time interval between "White" state and "Black" state. Rise time,  $T_r$ , is the time between photo detector output intensity changed from 90% to 10%. And fall time,  $T_f$ , is the time between photo detector output intensity changed from 10% to 90%.

Note 4: Definition of contrast ratio:

The contrast ratio is defined as the following expression.

$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD on the "White" state}}{\text{Luminance measured when LCD on the "Black" state}}$$

Note 5: White  $V_i = V_{i50} \pm 1.5V$

Black  $V_i = V_{i50} \pm 2.0V$

" $\pm$ " means that the analog input signal swings in phase with VCOM signal. " $\pm$ " means that the analog input signal swings out of phase with VCOM signal.

The 100% transmission is defined as the transmission of LCD panel when all the input terminals of module are electrically opened.

Note 6: Definition of color chromaticity (CIE 1931)

Color coordinates measured at the center point of LCD

Note 7: Measured at the center area of the panel when all the input terminals of LCD panel are electrically opened.

## **8.Interface**


### **8.1. LCM 40-PIN Definition - (8/16/18 bits) interface FPC 40 Contacts 0.5mm Top contact**

| PIN | SYMBOL           | FUNCTION                                            | REMARK           |
|-----|------------------|-----------------------------------------------------|------------------|
| 1   | GND              | GROUND: 0.0V                                        | LCD              |
| 2   | VDD              | POWER: +3.3V                                        | LCD              |
| 3   | BL_E             | BACKLIGHT CONTROL SIGNAL: L-OFF / H-ON              | LCD              |
| 4   | RS               | DATA/COMMAND SELECT                                 | LCD              |
| 5   | WR               | WRITE STROBE SIGNAL                                 | LCD              |
| 6   | RD               | READ STROBE SIGNAL                                  | LCD              |
| 7   | DB0              | DATA BUS                                            | LCD              |
| 8   | DB1              | DATA BUS                                            | LCD              |
| 9   | DB2              | DATA BUS                                            | LCD              |
| 10  | DB3              | DATA BUS                                            | LCD              |
| 11  | DB4              | DATA BUS                                            | LCD              |
| 12  | DB5              | DATA BUS                                            | LCD              |
| 13  | DB6              | DATA BUS                                            | LCD              |
| 14  | DB7              | DATA BUS                                            | LCD              |
| 15  | DB8              | DATA BUS                                            | LCD              |
| 16  | DB9              | DATA BUS                                            | LCD              |
| 17  | DB10             | DATA BUS                                            | LCD              |
| 18  | DB11             | DATA BUS                                            | LCD              |
| 19  | DB12             | DATA BUS                                            | LCD              |
| 20  | DB13             | DATA BUS                                            | LCD              |
| 21  | DB14             | DATA BUS                                            | LCD              |
| 22  | DB15             | DATA BUS                                            | LCD              |
| 23  | DB16             | DATA BUS                                            | LCD              |
| 24  | DB17             | DATA BUS                                            | LCD              |
| 25  | CS               | CHIP SELECT                                         | LCD              |
| 26  | NC               | NO CONNECTION                                       |                  |
| 27  | DISP_ON / IRQ_TP | DISPLAY ON_OFF / INTERRUPTION SIGNAL FOR TOUCHPANEL | TOUCH PANEL      |
| 28  | RES              | HARDWARE RESET                                      | LCD              |
| 29  | XL / DOUT_TP     | LEFT ELECTRODE / DATA OUT FOR TOUCHPANEL            | TOUCH PANEL      |
| 30  | YU / CS_TP       | UP ELECTRODE / CHIP SELECT FOR TOUCHPANEL           | TOUCH PANEL      |
| 31  | XR / DCLK_TP     | RIGHT ELECTRODE / CLOCK FOR TOUCHPANEL              | TOUCH PANEL      |
| 32  | YD / BUSY_TP     | DOWN ELECTRODE / BUSY SIGNAL FOR TOUCHPANEL         | TOUCH PANEL      |
| 33  | DIN_TP           | DATA IN FOR TOUCHPANEL                              | TOUCH PANEL      |
| 34  | GPIO1 / DOUT_RFM | GENERAL PURPOSE IO / DATA OUT FOR RF MODULE         | IO1 / RFM        |
| 35  | SCL              | CLOCK FOR I <sup>2</sup> C                          | I <sup>2</sup> C |
| 36  | SDA              | DATA FOR I <sup>2</sup> C                           | I <sup>2</sup> C |
| 37  | CS_SD            | CHIP SELECT FOR SD CARD                             | SD CARD          |
| 38  | DIN_SD           | DATA IN FOR SD CARD                                 | SD CARD          |
| 39  | CLK_SD           | CLOCK FOR SD CARD                                   | SD CARD          |
| 40  | DOUT_SD          | DATA OUT FOR SD CARD                                | SD CARD          |

## 8.2. LCM 24-PIN Definition (8-bits interface) FPC 20/24 Contacts 1mm Top contact (Optional)


| PIN | SYMBOL           | FUNCTION                                            | REMARK      |
|-----|------------------|-----------------------------------------------------|-------------|
| 1   | GND              | GROUND: 0.0V                                        | LCD         |
| 2   | VDD              | POWER: +3.3V                                        | LCD         |
| 3   | BL_E             | BACKLIGHT CONTROL SIGNAL: L-OFF / H-ON              | LCD         |
| 4   | RS               | DATA/COMMAND SELECT                                 | LCD         |
| 5   | WR               | WRITE STROBE SIGNAL                                 | LCD         |
| 6   | RD               | READ STROBE SIGNAL                                  | LCD         |
| 7   | DB0              | DATA BUS                                            | LCD         |
| 8   | DB1              | DATA BUS                                            | LCD         |
| 9   | DB2              | DATA BUS                                            | LCD         |
| 10  | DB3              | DATA BUS                                            | LCD         |
| 11  | DB4              | DATA BUS                                            | LCD         |
| 12  | DB5              | DATA BUS                                            | LCD         |
| 13  | DB6              | DATA BUS                                            | LCD         |
| 14  | DB7              | DATA BUS                                            | LCD         |
| 15  | CS               | CHIP SELECT                                         | LCD         |
| 16  | NC               | NO CONNECTION                                       |             |
| 17  | RES              | HARDWARE RESET                                      | LCD         |
| 18  | XL / DOUT_TP     | LEFT ELECTRODE / DATA OUT FOR TOUCHPANEL            | TOUCH PANEL |
| 19  | DISP_ON / IRQ_TP | DISPLAY ON_OFF / INTERRUPTION SIGNAL FOR TOUCHPANEL | TOUCH PANEL |
| 20  | YU / CS_TP       | UP ELECTRODE / CHIP SELECT FOR TOUCHPANEL           | TOUCH PANEL |
| 21  | XR / DCLK_TP     | RIGHT ELECTRODE / CLOCK FOR TOUCHPANEL              | TOUCH PANEL |
| 22  | YD / BUSY_TP     | DOWN ELECTRODE / BUSY SIGNAL FOR TOUCHPANEL         | TOUCH PANEL |
| 23  | DIN_TP           | DATA IN FOR TOUCHPANEL                              | TOUCH PANEL |
| 24  | GPIO1 / DOUT_RFM | GENERAL PURPOSE IO / DATA OUT FOR RF MODULE         | IO1 / RFM   |

## 9. Block Diagram



# 10. Reliability

Content of Reliability Test (Wide temperature, -20°C~70°C)

| Environmental Test                                                                                              |                                                                                                                                    |                                                                                                                                   |      |
|-----------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|------|
| Test Item                                                                                                       | Content of Test                                                                                                                    | Test Condition                                                                                                                    | Note |
| High Temperature Storage                                                                                        | Endurance test applying the high storage temperature for a long time.                                                              | 80°C<br>200hrs                                                                                                                    | 2    |
| Low Temperature Storage                                                                                         | Endurance test applying the low storage temperature for a long time.                                                               | -30°C<br>200hrs                                                                                                                   | 1,2  |
| High Temperature Operation                                                                                      | Endurance test applying the electric stress (Voltage & Current) and the thermal stress to the element for a long time              | 70°C<br>200hrs                                                                                                                    | -    |
| Low Temperature Operation                                                                                       | Endurance test applying the electric stress under low temperature for a long time                                                  | -20°C<br>200hrs                                                                                                                   | 1    |
| High Temperature Humidity Operation                                                                             | The module should be allowed to stand at 60°C,90%RH max                                                                            | 60°C,90%RH<br>96hrs                                                                                                               | 1,2  |
| <br>Thermal Shock Resistance | The sample should be allowed stand the following 10 cycles of operation<br>-20°C    25°C    70°C<br><br>30mim 5mim 30mim<br>1cicle | -20°C/70°C<br>10 cycles                                                                                                           | -    |
| Vibration test                                                                                                  | Endurance test applying the vibration during transportation and using                                                              | Total fixed amplitude:15mm<br>Vibration<br>Frequency:10~55Hz<br>One cycle 60 seconds to 3 directions of X,Y,Z for Each 15 minutes | 3    |
| Static electricity test                                                                                         | Endurance test applying the electric stress to the terminal                                                                        | VS=800V<br>RS=1.5kΩ<br>CS=100pF<br>1 time                                                                                         | -    |

Note1: No dew condensation to be observed.

Note2: The function test shall be conducted after 4 hours storage at the normal Temperature and humidity after remove from the test chamber

Note3: The packing has to including into the vibration testing.

## **11.Touch Panel Information**


### **11.1. Resistance Touch Panel General Specifications**

| ITEM                                             | DESCRIPTION                     |
|--------------------------------------------------|---------------------------------|
| Driving condition                                | DC5V                            |
| Operating force                                  | 60~150g                         |
| Linearity max                                    | $\leq \pm 1.5\%$                |
| Insulating resistance                            | $> 20\text{M}\Omega$ , 25V (DC) |
| Light transparence                               | 70%                             |
| Structure type                                   | ITO Film/ITO Glass(F/G)         |
| Surface Hardness                                 | 3H Typ                          |
| Pen Hitting Durability (with the silicon rubber) | $> 1000,000$ times              |
| X resistance                                     | 200~1100 $\Omega$               |
| Y resistance                                     | 200~1100 $\Omega$               |


**12. Contour Drawing**




**Front View**







**Side View**




**Back View**




**Isometric View**



| PIN | Name                |
|-----|---------------------|
| 1   | GND                 |
| 2   | +3.3V               |
| 3   | BLE(LCD)            |
| 4   | RS(LCD)             |
| 5   | WR(LCD)             |
| 6   | RD(LCD)             |
| 7   | DB0(LCD)            |
| 8   | DB1(LCD)            |
| 9   | DB2(LCD)            |
| 10  | DB3(LCD)            |
| 11  | DB4(LCD)            |
| 12  | DB5(LCD)            |
| 13  | DB6(LCD)            |
| 14  | DB7(LCD)            |
| 15  | DB8(LCD)            |
| 16  | DB9(LCD)            |
| 17  | DB10(LCD)           |
| 18  | DB11(LCD)           |
| 19  | DB12(LCD)           |
| 20  | DB13(LCD)           |
| 21  | DB14(LCD)           |
| 22  | DB15(LCD)           |
| 23  | DB16(LCD)           |
| 24  | DB17(LCD)           |
| 25  | CS(LCD)             |
| 26  | N/C                 |
| 27  | DISPON(LCD)/IRQ(TP) |
| 28  | RST(LCD)            |
| 29  | L/DOUT(TP)          |
| 30  | U/CS(TP)            |
| 31  | R/DCLK(TP)          |
| 32  | D/BUSY(TP)          |
| 33  | DIN(TP)             |
| 34  | DIO1                |
| 35  | SCL(I2C)            |
| 36  | SDA(I2C)            |
| 37  | CS(SD)              |
| 38  | DI(TP)              |
| 39  | CK(TP)              |
| 40  | DO(TP)              |



13.Additional Resources



| DESCRIPTION |                 |                                      | STD | OPC |
|-------------|-----------------|--------------------------------------|-----|-----|
| 01          | CN1             | 8/16/18 Bits Interface               | X   |     |
| 02          | CN2             | 8 Bits Interface                     |     | X   |
| 03          | CN7             | Micro SD Holder                      |     | X   |
| 04          | BTM             | Bluetooth Module 4.2 Low Energy      |     | X   |
| 05          | U6              | MCU 8051 Core                        |     | X   |
| 06          | U9              | Level Converter for UART             |     | X   |
| 07          | RFM             | RF 433.92MHz Module                  |     | X   |
| 08          | U10             | Real Time Clock (RTC)                |     | X   |
| 09          | CN8             | UART/GPIO Interface                  |     | X   |
| 10          | CN5             | 3.5" LCD Interface                   | X   |     |
| 11          | U5              | Touchscreen Controller               |     | X   |
| 12          | V6/V7/V8/V9     | TVS for Circuit Break                |     | X   |
| 13          | C52/C53/C54/C55 | Capacitor for Circuit Break          |     | X   |
| 14          | U1              | LCD-TFT Controller                   | X   |     |
| 15          | BZ              | Buzzer                               |     | X   |
| 16          | BAT             | Real Time Clock (RTC) Battery Holder |     | X   |

| CN8 - UART/GPIO INTERFACE |           |
|---------------------------|-----------|
| 01                        | GND       |
| 02                        | +5VDC     |
| 03                        | TX (UART) |
| 04                        | RX (UART) |
| 05                        | GPIO4     |
| 06                        | GPIO3     |
| 07                        | GPIO2     |
| 08                        | GPIO1     |

## **14. Code System AGT TFT**

### **14.1. Standard**

|          | 1<br>AG                          | 2<br>M - | 3<br>035 | 4<br>A | 5<br>0 | 6<br>- | 7<br>D | 8 - Additional<br>0 - R |
|----------|----------------------------------|----------|----------|--------|--------|--------|--------|-------------------------|
| <b>1</b> | <b>AGTechnologies</b>            |          |          |        |        |        |        |                         |
| <b>2</b> | M: TFT + Control Board           |          |          |        |        |        |        |                         |
| <b>3</b> | <b>Display size</b>              |          |          |        |        |        |        |                         |
|          | 035: 3,5"                        |          |          |        |        |        |        |                         |
|          | 043: 4.3"                        |          |          |        |        |        |        |                         |
|          | 057: 5.7"                        |          |          |        |        |        |        |                         |
|          | 070: 7.0"                        |          |          |        |        |        |        |                         |
|          | 101: 10.1"                       |          |          |        |        |        |        |                         |
|          | 104: 10.4"                       |          |          |        |        |        |        |                         |
| <b>4</b> | <b>Internal Code</b>             |          |          |        |        |        |        |                         |
|          |                                  |          |          |        |        |        |        |                         |
| <b>5</b> | <b>Display model</b>             |          |          |        |        |        |        |                         |
|          |                                  |          |          |        |        |        |        |                         |
| <b>6</b> | <b>Control Board</b>             |          |          |        |        |        |        |                         |
|          | D: Data Control Board            |          |          |        |        |        |        |                         |
|          | V: VGA Control Board             |          |          |        |        |        |        |                         |
|          | C: Composite Video Control Board |          |          |        |        |        |        |                         |
|          | A: Android Control Board         |          |          |        |        |        |        |                         |
| <b>7</b> | <b>Control Board Model</b>       |          |          |        |        |        |        |                         |
|          | 0, 1, 2, 3, 4, 5...              |          |          |        |        |        |        |                         |
| <b>8</b> | <b>TouchPanel Model</b>          |          |          |        |        |        |        |                         |
|          | N: No Touchscreen                |          |          |        |        |        |        |                         |
|          | R: Resistive Touchscreen         |          |          |        |        |        |        |                         |
|          | C: Capacitive Touchscreen        |          |          |        |        |        |        |                         |
|          | P: Projected Touchscreen         |          |          |        |        |        |        |                         |

## 14.2. Additional resources (Optional)

|          | T R B PAH S C M 0ZU K<br>AGM-035A0-D0-R - 1 2 3 3.1 4 5 6 6.1 7                                                                                                                                                                    |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>1</b> | <b>T</b> = SPI Touch Controller                                                                                                                                                                                                    |
| <b>2</b> | <b>R</b> = Radio Frequency Module                                                                                                                                                                                                  |
| <b>3</b> | <b>B</b> = Bluetooth Low Energy module<br><br><b>3.1:</b><br><b>P</b> = Pressure Sensor<br><b>A</b> = Accelerometer<br><b>H</b> = Humidity / Temperature Sensor                                                                    |
| <b>4</b> | <b>S</b> = MicroSD / TF Card                                                                                                                                                                                                       |
| <b>5</b> | <b>C</b> = RTC (Real Time Clock)                                                                                                                                                                                                   |
| <b>6</b> | <b>M</b> = Module MCU 8051<br><br><b>6.1:</b><br><b>Z</b> = Buzzer<br><b>U</b> = UART Communication                                                                                                                                |
| <b>7</b> | <b>K</b> = Development Kit = (1+3)<br><b>FC</b> = (1+2)<br><b>F</b> = 1<br><b>C</b> = 2<br><br>1 = Flat 40 contacts / 0.5mm pitch / 200mm length<br>2 = Connector FPC 40 contacts TOP / 0.5mm pitch / SMD<br>3 = FPC ADAPTER BOARD |

## **15. Kit Information**



40 pins FPC 0.5mm for DIP 2.54mm.