

SPECIFICATION

AGO-050S0-NN-R

Record of Revision

Version	Revise Date	Page	Content
Pre-spec.A	2014/12/26		Initial Release

Contents

1. General Specifications	4
2. Pin Assignment	5
3. Operation Specifications	7
3.1. Absolute Maximum Rating	7
3.1.1. Typical Operation Conditions	8
3.1.2. Backlight Drving Conditions	8
3.2. Power Sequence	9
3.3. Timing Characteristics	10
3.3.1. AC Electrical Characteristics	10
3.3.2. Input Clock and Data Timing Diagram	11
3.3.3. Timing	12
3.3.4. Data Input Format	13
4. Optical Specifications	15
5. Reliability Test Items	19
6. General Precautions	20
6.1. Safety	20
6.2. Handling	20
6.3. Static Electricity	20
6.4. Storage	20
6.5. Cleaning	20
7. Mechanical Drawing	21
8. Touch Panel Specification	22
8.1 Electrical Characteristics	22
8.2 Optical Characteristcs	22
8.3 Mechanical Characteristics	22
8.4 Mechanical Drawing	23

1. General Specifications

No.	Item	Specification	Remark
1	LCD Size	5.0 inch(Diagonal)	
2	Driver element	a-Si TFT active matrix	
3	Resolution	480 × 3(RGB) × 272	
4	Display mode	Normally White, Transmissive	
5	Dot pitch	0.066(W) X 0.198(H) mm	
6	Active area	110.880(W) X 3(RGB) X 62.832(H) mm	
7	Outline dimensions	120.7(H) X 76.3(V) X 3.9(D) mm	
8	Surface treatment	Anti-Glare	
9	Color arrangement	RGB-stripe	
10	Interface	TTL RGB-24bit parallel interface	
11	Backlight Power consumption	TBD	
12	Panel Power consumption	TBD	
13	Weight	TBD	

2. Pin Assignment

FPC connector is used for electronics interface. The recommended model is FH19SC-40S-0.5SH (05) manufactured by HIROSE.

No.	Symbol	I/O	Function
1	VLED-	P	Power for LED backlight cathode
2	VLED+	P	Power for LED backlight anode
3	GND	P	Power ground
4	VDD	P	Power voltage
5	R0	I	Red data (LSB)
6	R1	I	Red data
7	R2	I	Red data
8	R3	I	Red data
9	R4	I	Red data
10	R5	I	Red data
11	R6	I	Red data
12	R7	I	Red data (MSB)
13	G0	I	Green data (LSB)
14	G1	I	Green data
15	G2	I	Green data
16	G3	I	Green data
17	G4	I	Green data
18	G5	I	Green data
19	G6	I	Green data
20	G7	I	Green data (MSB)
21	B0	I	Blue data (LSB)
22	B1	I	Blue data
23	B2	I	Blue data
24	B3	I	Blue data
25	B4	I	Blue data
26	B5	I	Blue data
27	B6	I	Blue data
28	B7	I	Blue data (MSB)
29	GND	P	Power ground
30	DCLK	I	Pixel clock
31	DISP	I	Display on/ off
32	HSYNC	I	Horizontal sync signal
33	VSYNC	I	Vertical sync signal
34	DE	I	Data enable
35	NC	-	No connect
36	GND	P	Power ground
37	X_R	I/O	Right electrode - differential analog

38	Y_B	I/O	Bottom electrode - differential analog
39	X_L	I/O	Left electrode - differential analog
40	Y_T	I/O	Top electrode - differential analog

I/O: I: input, O: output, P: power

3. Operation Specifications

3.1. Absolute Maximum Ratings

(Note 1)

Item	Symbol	Values		Unit	Remark
		Min.	Max.		
Supply voltage	V_{DD}	-0.3	4.5	V	
Operation Temperature	T_{OP}	-20	60	°C	
Storage Temperature	T_{ST}	-30	70	°C	

Note 1: The absolute maximum rating values of this product are not allowed to be exceeded at any times. Should a module be used with any of the absolute maximum ratings exceeded, the characteristics of the module may not be recovered, or in an extreme case, the module may be permanently destroyed.

3.1.1. Typical Operation Conditions


Item	Symbol	Values			Unit	Remark
		Min.	Typ	Max.		
Power voltage	V_{DD}	3.0	3.3	3.6	V	Note 2
Current for Driver	$I_{V_{DD}}$	-	17	25	mA	
Input logic high voltage	V_{IH}	$0.8 V_{DD}$	-	V_{DD}	V	Note 3
Input logic low voltage	V_{IL}	0	-	$0.2 V_{DD}$	V	

3.1.2. Backlight Driving Conditions (12 White Chips)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Supply voltage of white LED backlight	VL	17.4	19.8	21	V	Note 1
Current for LED backlight	IL	30	40	50	mA	
Luminance (on the module surface,BM-7)		150	200	-	cd/m ²	
LED life time	-	20,000	-	-	Hr	Note 2


Note 1: The LED Supply Voltage is defined by the number of LED at $T_a=25^{\circ}\text{C}$ and $I_L=40\text{mA}$.

Note 2: The “LED life time” is defined as the module brightness decrease to 50% original brightness at $T_a=25^{\circ}\text{C}$ and $I_L=40\text{mA}$. The LED lifetime could be decreased if operating I_L is larger than 40mA.




3.2. Power Sequence

Power On Sequence



Power Off Sequence





3.3. Timing Characteristics

3.3.1. AC Electrical Characteristics

AC Electrical Characteristics (VDDIO=VDD=3.0 to 3.6v, GND=0V, TA=-20 to +85 °C)

Parameters	Symbol	Min.	Typ.	Max.	Unit	Conditions
System operation timing						
VDD power source slew time	TPOR	-	-	20	ms	From 0V to 99% VDD
GRB pulse width	tRSTW	10	50	-	us	R=10Kohm, C=1uF
Input Output timing						
DCLK clock time	Tclk	33.3	-	-	ns	DCLK=30MHz
DCLK clock low period	Tcwl	40	-	60	%	
DCLK clock high period	Tcwh	40	-	60	%	
Clock rising time	Trck	9	-	-	ns	
Clock falling time	Tfck	9	-	-	ns	
HSD width	Thwh	1	-	-	DCLK	
HSD period time	Th	55	60	65	us	
HSD setup time	Thsu	12	-	-	ns	
HSD hold time	Thhd	12	-	-	ns	
VSD width	Tvwh	1	-	-	Th	
VSD setup time	Tvsu	12	-	-	ns	
VSD hold time	Tvhd	12	-	-	ns	
Data setup time	Tdasu	12	-	-	ns	
Data hold time	Tdahd	12	-	-	ns	
DE setup time	Tdesu	12	-	-	ns	
DE hold time	Tdehd	12	-	-	ns	
Source output setting time	Tsst	-	-	TBD	us	10% to 90% CL=60pF, RL=2Kohm
Gate output setting time	Tgst	-	-	TBD	ns	10% to 90%, CL=60pF
VCOM output setting time	Tcst	-	-	TBD	us	10% to 90%, CL=40nF, RL=50ohm
Time from VSD to 1st line data input	Tvs	3	8	31	Th	HV mode By HDL[4:0] setting
3-wire serial communication AC timing						
Serial clock	Tsck	200	-	-	ns	For SCL pin
SCL pulse low period	Tckl	40	-	60	%	
SCL pulse low period	Tckh	40	-	60	%	
Serial data setup time	Tisu	50	-	-	ns	
Serial data hold time	Tihd	50	-	-	ns	
Serial clock high/low	Tssw	50	-	-	ns	
CSB to VSD	Tcv	1			us	
CSB distinguish time	Tcd	400	-	-	ns	
CSB input setup time	Tcsu	50	-	-	ns	
CSB input hold time	Tchd	50	-	-	ns	

3.3.2. Input Clock and Data Timing Diagram



3.3.3. Timing

Vertical input timing

Parameters	Symbol	Min.	Typ.	Max.	Unit	Conditions
DCLK frequency	Fclk	24	27	30	MHz	
DCLK cycle time	Tclk	83	110	200	ns	
DCLK pulse duty	Tcwh	40	50	60	%	
Time from HSD to source output	Thso	-	13	-	DCLK	
Time from HSD to gate output	Thgo	-	27	-	DCLK	
Time from HSD to gate output off	Thgz	-	3	-	DCLK	
Time from HSD to VCOM	Thvc	-	12	-	DCLK	

Parallel RGB input timign table


Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
DCLK frequency	fclk	5	9	12	MHz
VSD period time	Tv	277	288	400	H
VSD display area	Tvd	272			H
VSD back porch	Tvb	3	8	31	H
VSD front porch	Tvfp	2	8	93	H
HSD period time	Th	520	525	800	DCLK
HSD display area	Thd	480			DCLK
HSD back porch	Thbp	36	40	255	DCLK
HSD front porch	Thfp	4	5	65	DCLK

Serial RGB input timign table


Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
DCLK frequency	fclk	-	27	-	MHz
VSD period time	Tv	277	288	400	H
VSD display area	Tvd	272			H
VSD back porch	Tvb	3	8	31	H
VSD front porch	Tvfp	2	8	93	H
HSD period time	Th	-	1575	-	DCLK
HSD display area	Thd	1440			DCLK
HSD back porch	Thbp	-	120	-	DCLK
HSD front porch	Thfp	-	15	-	DCLK

3.3.4. Data Input Format

Vertical input timing




Serial 8-bit RGB Mode Data format




Parallel RGB Mode Data format

(HV Mode)



(DE Mode)



4. Optical Specifications

Ta=25 °C

Item		Symbol	Condition	Min	Typ	Max	Unit	Remark
View Angles		θT	CR≥ 10	30	40	--	Degree	Note1
		θB		40	50	--		
		θL		40	50	--		
		θR		40	50	--		
Contrast Ratio		CR	θ=0°	350	500	--		Note4
Response Time		T _{ON}	25℃	--	25	40	ms	Note3
		T _{OFF}						
Chromaticity	White	x	Backlight is on	0.278	0.298	0.318		Note2 Note5 Note6
		y		0.307	0.327	0.347		
	Red	x		0.585	0.605	0.625		
		y		0.311	0.331	0.351		
	Green	x		0.269	0.289	0.309		
		y		0.526	0.546	0.566		
	Blue	x		0.121	0.141	0.161		
		y		0.109	0.129	0.149		
Uniformity		U		75	80	--	%	Note7
NTSC				--	50	--	%	
Luminance		L		150	200	--	cd/m ²	Note6

Test Conditions:

1. $DV_{DD}=3.3V$, $I_L=40mA$ (Backlight current),the ambient temperature is 25 °C .
2. The test systems refer to Note 2.

Note 1: Definition of viewing angle range




Fig. 4-1 Definition of viewing angle

Note 2: Definition of optical measurement system.

The optical characteristics should be measured in dark room. After 30 minutes operation, the optical properties are measured at the center point of the LCD screen. (Response time is measured by Photo detector TOPCON BM-7, other items are measured by BM-5A/Field of view: 1° /Height: 500mm.)




Fig. 4-2 Optical measurement system setup

Note 3: Definition of Response time

The response time is defined as the LCD optical switching time interval between "White" state and "Black" state. Rise time (T_{ON}) is the time between photo detector output intensity changed from 90% to 10%. And fall time (T_{OFF}) is the time between photo detector output intensity changed from 10% to 90%.




Fig. 4-3 Definition of response time

Note 4: Definition of contrast ratio

$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD on the "White" state}}{\text{Luminance measured when LCD on the "Black" state}}$$

Note 5: Definition of color chromaticity (CIE1931)

Color coordinates measured at center point of LCD.

Note 6: All input terminals LCD panel must be ground while measuring the center area of the panel.

Note 7: Definition of Luminance Uniformity

Active area is divided into 9 measuring areas (Refer to Fig. 4-4).Every measuring point is placed at the center of each measuring area.

$$\text{Luminance Uniformity (Yu)} = \frac{B_{min}}{B_{max}}$$

L-----Active area length W----- Active area width




Fig. 4-4 Definition of measuring points

B_{max} : The measured maximum luminance of all measurement position.

B_{min} : The measured minimum luminance of all measurement position.

5. Reliability Test Items

(Note3)

Item	Test Conditions	Remark
High Temperature Storage	Ta = 80℃ 240hrs	Note 1 , Note 4
Low Temperature Storage	Ta = -30℃ 240hrs	Note 1 , Note 4
High Temperature Operation	Ts = 70℃ 240hrs	Note 2 , Note 4
Low Temperature Operation	Ta = -20℃ 240hrs	Note 1 , Note 4
Operate at High Temperature and Humidity	+60℃, 90%RH 240hrs	Note 4
Thermal Shock	-30℃/30 min ~ +80℃/30 min for a total 100 cycles, Start with cold temperature and end with high temperature.	Note 4
Vibration Test	Frequency range:10~55Hz Stroke:1.5mm Sweep:10Hz~55Hz~10Hz 2 hours for each direction of X. Y. Z. (6 hours for total)	
Mechanical Shock	100G 6ms,±X, ±Y, ±Z 3 times for each direction	
Package Vibration Test	Random Vibration : 0.015G*G/Hz from 5-200HZ, -6dB/Octave from 200-500HZ 2 hours for each direction of X. Y. Z. (6 hours for total)	
Package Drop Test	Height:60 cm 1 corner, 3 edges, 6 surfaces	
Electro Static Discharge	Contact:±6KV,Air:±8KV 150pF , 330 Ω ,	Note 5

Note 1: Ta is the ambient temperature of samples.

Note 2: Ts is the temperature of panel's surface.

Note 3: In the standard condition, there shall be no practical problem that may affect the display function. After the reliability test, the product only guarantees operation, but don't guarantee all of the cosmetic specification.

Note 4: Before cosmetic and function test, the product must have enough recovery time, at least 2 hours at room temperature.

Note 5: LCD glass and metal bezel .

6. General Precautions

6.1. Safety

Liquid crystal is poisonous. Do not put it in your mouth. If liquid crystal touches your skin or clothes, wash it off immediately by using soap and water.

6.2. Handling

1. The LCD panel is plate glass. Do not subject the panel to mechanical shock or to excessive force on its surface.
2. The polarizer attached to the display is easily damaged. Please handle it carefully to avoid scratch or other damages.
3. To avoid contamination on the display surface, do not touch the module surface with bare hands.
4. Keep a space so that the LCD panels do not touch other components.
5. Put cover board such as acrylic board on the surface of LCD panel to protect panel from damages.
6. Transparent electrodes may be disconnected if you use the LCD panel under environmental conditions where the condensation of dew occurs.
7. Do not leave module in direct sunlight to avoid malfunction of the ICs.

6.3. Static Electricity

1. Be sure to ground module before turning on power or operating module.
2. Do not apply voltage which exceeds the absolute maximum rating value.


6.4. Storage

1. Store the module in a dark room where must keep at $25\pm10^{\circ}\text{C}$ and 65%RH or less.
2. Do not store the module in surroundings containing organic solvent or corrosive gas.
3. Store the module in an anti-electrostatic container or bag.

6.5. Cleaning

1. Do not wipe the polarizer with dry cloth. It might cause scratch.
2. Only use a soft cloth with IPA to wipe the polarizer, other chemicals might permanent damage to the polarizer.

7. Mechanical Drawing



Specification:

- 1). Viewing angle: 6 0' clock
- 2). Display mode: a Si TFT/Transmissive/Normal White
- 3). Operating temp.: -20° C~+70° C
Storage temp.: -30° C~+80° C
- 4). IC: ILI6480BQ
- 5). All the raw material are Rohs compliant

FFC排线R5=空=DE
FFC排线R5=1K=VSD
TP=SZTP1040-5

8.Touch Panel Specification

8.1 Electrical Characteristics

Item	Value			Unit	Remark
	Min.	Typ.	Max.		
Lineanty	-1.5	-	+1.5	%	Afterenvinronment andlifelest
TerminalResistance	300	-	1000	Ω	X(Glassside)
	100	-	500	Ω	Y(Glassside)
Insulation Resistance	20	-	-	M Ω	DC25V1min
OperatingVoltage	-	5	-	V	DC

8.2 Optical Characteristics

Item	Value			Unit	Remark
	Min.	Typ.	Max.		
ResponseTime	-	-	10	ms	100K Ω pull-up
LightTransparency	78	-	-	%	-

8.3 Mechanical Characteristics

Item	Value			Unit	Remark
	Min.	Typ.	Max.		
ActiveForce	30	-	100	g	
SurfaceHardness	3	-	-	H	
PenSlidingDurability	100.000	-	-	time	
HittingDurability	1.000.000	-	-	time	

Technical drawing of a sensor module, showing top, side, and detail views with dimensions and specifications.

Top View Dimensions:

- Overall dimensions: 117.40 TP, 113.40 VA, 111.20 AA, 63.20 AA, 64.20 VA, 70.00 TP.
- Internal dimensions: 117.20背胶外框, 1.20, 4.60±0.50, 1.20, 2.50, 69.80背胶外框.
- Regions: X+, X-, Y+, Y-.
- Material: 背胶 T=0.1MM.

Side View Dimensions:

- Overall height: 1.140.1.
- Internal height: 1.120.0.
- Material: TOP ITO Film 0.188mm, BOTTOM ITO Glass 0.7mm.
- Seal: 密封胶.
- Pin dimensions: 28.50±0.5, 8±0.60, 5.60, 5.00±0.3, 4.50±0.3, 0.140.05.
- Pin material: 3046T T=0.03MM.

Detail View Dimensions:

- Overall dimensions: 4.00±0.3, 6.50±0.5, 2.50±0.1, 2.00±0.15, W:0.50±0.05, P:1.30±0.1.
- Regions: X+, X-, Y+, Y-.
- Material: 背胶 T=0.1MM.

Technical Requirements:

- 材料特性: 1. 上电极: 单层雾面防牛0.188mm; 2. 下电极: 普通ITO Glass 厚度: 0.7mm.
- 环境参数: 1. 工作温度: -10° C ~ 60° C; 2. 储存温度: -20° C ~ 70° C.
- 耐久性: 1. 打点寿命: 250gf, 2次/秒, ≥1,000,000次; 2. 操作压力: 30~100g.
- 机械性能: 1. 表面硬度: 3H; 2. 光学性能: 透光率 ≥ 78%; 3. 电性能: 1. 线性度: ≤ 1.5% Y; 2. 电阻: ≤ 1.5% Y; 3. 电阻: ≤ 1.5% Y; 4. 电阻: ≤ 1.5% Y; 5. 电阻: ≤ 1.5% Y; 6. 电阻: ≤ 1.5% Y; 7. 电阻: ≤ 1.5% Y; 8. 电阻: ≤ 1.5% Y; 9. 电阻: ≤ 1.5% Y; 10. 电阻: ≤ 1.5% Y; 11. 电阻: ≤ 1.5% Y; 12. 电阻: ≤ 1.5% Y; 13. 电阻: ≤ 1.5% Y; 14. 电阻: ≤ 1.5% Y; 15. 电阻: ≤ 1.5% Y; 16. 电阻: ≤ 1.5% Y; 17. 电阻: ≤ 1.5% Y; 18. 电阻: ≤ 1.5% Y; 19. 电阻: ≤ 1.5% Y; 20. 电阻: ≤ 1.5% Y; 21. 电阻: ≤ 1.5% Y; 22. 电阻: ≤ 1.5% Y; 23. 电阻: ≤ 1.5% Y; 24. 电阻: ≤ 1.5% Y; 25. 电阻: ≤ 1.5% Y; 26. 电阻: ≤ 1.5% Y; 27. 电阻: ≤ 1.5% Y; 28. 电阻: ≤ 1.5% Y; 29. 电阻: ≤ 1.5% Y; 30. 电阻: ≤ 1.5% Y; 31. 电阻: ≤ 1.5% Y; 32. 电阻: ≤ 1.5% Y; 33. 电阻: ≤ 1.5% Y; 34. 电阻: ≤ 1.5% Y; 35. 电阻: ≤ 1.5% Y; 36. 电阻: ≤ 1.5% Y; 37. 电阻: ≤ 1.5% Y; 38. 电阻: ≤ 1.5% Y; 39. 电阻: ≤ 1.5% Y; 40. 电阻: ≤ 1.5% Y; 41. 电阻: ≤ 1.5% Y; 42. 电阻: ≤ 1.5% Y; 43. 电阻: ≤ 1.5% Y; 44. 电阻: ≤ 1.5% Y; 45. 电阻: ≤ 1.5% Y; 46. 电阻: ≤ 1.5% Y; 47. 电阻: ≤ 1.5% Y; 48. 电阻: ≤ 1.5% Y; 49. 电阻: ≤ 1.5% Y; 50. 电阻: ≤ 1.5% Y; 51. 电阻: ≤ 1.5% Y; 52. 电阻: ≤ 1.5% Y; 53. 电阻: ≤ 1.5% Y; 54. 电阻: ≤ 1.5% Y; 55. 电阻: ≤ 1.5% Y; 56. 电阻: ≤ 1.5% Y; 57. 电阻: ≤ 1.5% Y; 58. 电阻: ≤ 1.5% Y; 59. 电阻: ≤ 1.5% Y; 60. 电阻: ≤ 1.5% Y; 61. 电阻: ≤ 1.5% Y; 62. 电阻: ≤ 1.5% Y; 63. 电阻: ≤ 1.5% Y; 64. 电阻: ≤ 1.5% Y; 65. 电阻: ≤ 1.5% Y; 66. 电阻: ≤ 1.5% Y; 67. 电阻: ≤ 1.5% Y; 68. 电阻: ≤ 1.5% Y; 69. 电阻: ≤ 1.5% Y; 70. 电阻: ≤ 1.5% Y; 71. 电阻: ≤ 1.5% Y; 72. 电阻: ≤ 1.5% Y; 73. 电阻: ≤ 1.5% Y; 74. 电阻: ≤ 1.5% Y; 75. 电阻: ≤ 1.5% Y; 76. 电阻: ≤ 1.5% Y; 77. 电阻: ≤ 1.5% Y; 78. 电阻: ≤ 1.5% Y; 79. 电阻: ≤ 1.5% Y; 80. 电阻: ≤ 1.5% Y; 81. 电阻: ≤ 1.5% Y; 82. 电阻: ≤ 1.5% Y; 83. 电阻: ≤ 1.5% Y; 84. 电阻: ≤ 1.5% Y; 85. 电阻: ≤ 1.5% Y; 86. 电阻: ≤ 1.5% Y; 87. 电阻: ≤ 1.5% Y; 88. 电阻: ≤ 1.5% Y; 89. 电阻: ≤ 1.5% Y; 90. 电阻: ≤ 1.5% Y; 91. 电阻: ≤ 1.5% Y; 92. 电阻: ≤ 1.5% Y; 93. 电阻: ≤ 1.5% Y; 94. 电阻: ≤ 1.5% Y; 95. 电阻: ≤ 1.5% Y; 96. 电阻: ≤ 1.5% Y; 97. 电阻: ≤ 1.5% Y; 98. 电阻: ≤ 1.5% Y; 99. 电阻: ≤ 1.5% Y; 100. 电阻: ≤ 1.5% Y; 101. 电阻: ≤ 1.5% Y; 102. 电阻: ≤ 1.5% Y; 103. 电阻: ≤ 1.5% Y; 104. 电阻: ≤ 1.5% Y; 105. 电阻: ≤ 1.5% Y; 106. 电阻: ≤ 1.5% Y; 107. 电阻: ≤ 1.5% Y; 108. 电阻: ≤ 1.5% Y; 109. 电阻: ≤ 1.5% Y; 110. 电阻: ≤ 1.5% Y; 111. 电阻: ≤ 1.5% Y; 112. 电阻: ≤ 1.5% Y; 113. 电阻: ≤ 1.5% Y; 114. 电阻: ≤ 1.5% Y; 115. 电阻: ≤ 1.5% Y; 116. 电阻: ≤ 1.5% Y; 117. 电阻: ≤ 1.5% Y; 118. 电阻: ≤ 1.5% Y; 119. 电阻: ≤ 1.5% Y; 120. 电阻: ≤ 1.5% Y; 121. 电阻: ≤ 1.5% Y; 122. 电阻: ≤ 1.5% Y; 123. 电阻: ≤ 1.5% Y; 124. 电阻: ≤ 1.5% Y; 125. 电阻: ≤ 1.5% Y; 126. 电阻: ≤ 1.5% Y; 127. 电阻: ≤ 1.5% Y; 128. 电阻: ≤ 1.5% Y; 129. 电阻: ≤ 1.5% Y; 130. 电阻: ≤ 1.5% Y; 131. 电阻: ≤ 1.5% Y; 132. 电阻: ≤ 1.5% Y; 133. 电阻: ≤ 1.5% Y; 134. 电阻: ≤ 1.5% Y; 135. 电阻: ≤ 1.5% Y; 136. 电阻: ≤ 1.5% Y; 137. 电阻: ≤ 1.5% Y; 138. 电阻: ≤ 1.5% Y; 139. 电阻: ≤ 1.5% Y; 140. 电阻: ≤ 1.5% Y; 141. 电阻: ≤ 1.5% Y; 142. 电阻: ≤ 1.5% Y; 143. 电阻: ≤ 1.5% Y; 144. 电阻: ≤ 1.5% Y; 145. 电阻: ≤ 1.5% Y; 146. 电阻: ≤ 1.5% Y; 147. 电阻: ≤ 1.5% Y; 148. 电阻: ≤ 1.5% Y; 149. 电阻: ≤ 1.5% Y; 150. 电阻: ≤ 1.5% Y; 151. 电阻: ≤ 1.5% Y; 152. 电阻: ≤ 1.5% Y; 153. 电阻: ≤ 1.5% Y; 154. 电阻: ≤ 1.5% Y; 155. 电阻: ≤ 1.5% Y; 156. 电阻: ≤ 1.5% Y; 157. 电阻: ≤ 1.5% Y; 158. 电阻: ≤ 1.5% Y; 159. 电阻: ≤ 1.5% Y; 160. 电阻: ≤ 1.5% Y; 161. 电阻: ≤ 1.5% Y; 162. 电阻: ≤ 1.5% Y; 163. 电阻: ≤ 1.5% Y; 164. 电阻: ≤ 1.5% Y; 165. 电阻: ≤ 1.5% Y; 166. 电阻: ≤ 1.5% Y; 167. 电阻: ≤ 1.5% Y; 168. 电阻: ≤ 1.5% Y; 169. 电阻: ≤ 1.5% Y; 170. 电阻: ≤ 1.5% Y; 171. 电阻: ≤ 1.5% Y; 172. 电阻: ≤ 1.5% Y; 173. 电阻: ≤ 1.5% Y; 174. 电阻: ≤ 1.5% Y; 175. 电阻: ≤ 1.5% Y; 176. 电阻: ≤ 1.5% Y; 177. 电阻: ≤ 1.5% Y; 178. 电阻: ≤ 1.5% Y; 179. 电阻: ≤ 1.5% Y; 180. 电阻: ≤ 1.5% Y; 181. 电阻: ≤ 1.5% Y; 182. 电阻: ≤ 1.5% Y; 183. 电阻: ≤ 1.5% Y; 184. 电阻: ≤ 1.5% Y; 185. 电阻: ≤ 1.5% Y; 186. 电阻: ≤ 1.5% Y; 187. 电阻: ≤ 1.5% Y; 188. 电阻: ≤ 1.5% Y; 189. 电阻: ≤ 1.5% Y; 190. 电阻: ≤ 1.5% Y; 191. 电阻: ≤ 1.5% Y; 192. 电阻: ≤ 1.5% Y; 193. 电阻: ≤ 1.5% Y; 194. 电阻: ≤ 1.5% Y; 195. 电阻: ≤ 1.5% Y; 196. 电阻: ≤ 1.5% Y; 197. 电阻: ≤ 1.5% Y; 198. 电阻: ≤ 1.5% Y; 199. 电阻: ≤ 1.5% Y; 200. 电阻: ≤ 1.5% Y; 201. 电阻: ≤ 1.5% Y; 202. 电阻: ≤ 1.5% Y; 203. 电阻: ≤ 1.5% Y; 204. 电阻: ≤ 1.5% Y; 205. 电阻: ≤ 1.5% Y; 206. 电阻: ≤ 1.5% Y; 207. 电阻: ≤ 1.5% Y; 208. 电阻: ≤ 1.5% Y; 209. 电阻: ≤ 1.5% Y; 210. 电阻: ≤ 1.5% Y; 211. 电阻: ≤ 1.5% Y; 212. 电阻: ≤ 1.5% Y; 213. 电阻: ≤ 1.5% Y; 214. 电阻: ≤ 1.5% Y; 215. 电阻: ≤ 1.5% Y; 216. 电阻: ≤ 1.5% Y; 217. 电阻: ≤ 1.5% Y; 218. 电阻: ≤ 1.5% Y; 219. 电阻: ≤ 1.5% Y; 22